

Type 4060 DC-S





Bestell-Nr. 1002 5548	
Anwendungen	Bohren, Fräsen, Schleifen, Gravieren
Spanndurchmesser	60 mm
Motorart	Drehstromsynchronmotor
Drehzahlbereich	2.500 - 60.000 min ⁻¹
Spannung	230 V
Strom	max. 12 A
Drehmoment	max. 65 Ncm
Frequenz	33 - 1.000 Hz
Leistung	max. 3.000 W
Gewicht	3,3 kg
Lagerung	3 x Hybrid, lebensdauergeschmiert
Schutzart	IP 54
Motorschutz	PTC - 100 °C
Gebrauchslage	
Belastungsrichtung	axial + radial
Rundlauf (Kegel)	≤ 1,5 µm
Spannzangenbereich	Ø 1,0 - 6,35 mm (incl. 1/8 + 1/4")
Werkzeugwechsel	2 Ring-Maulschlüssel (SW 10 + 13)
Kühlsystem	Kühlung durch Einspannvorrichtung
Geschützt gegen Schmutz und Kühlschmiermittel	Sperrluft 0,5 - 0,8 bar (Schlauch Ø innen/außen 4/6 mm)
Gehäusematerial	Edelstahl
Umrichterempfehlung	e@syDrive® 4438, TV 4538

Änderungen vorbehalten

Part No. 1002 5548	
Applications	Drilling, Milling, Grinding, Engraving
Clamping diameter	60 mm
Motor system	Brushless DC motor (BLDC)
Speed range	2,500 - 60,000 rpm
Voltage	230 V
Current	max. 12 A
Torque	max. 65 Ncm
Frequency	33 - 1,000 Hz
Output power	max. 3,000 W
Weight	3.3 kg
Bearing system	3 x Hybrid, lifetime lubrication
Protection category	IP 54
Motor protection	PTC - 100°C
Working position	
Load direction	axial + radial
Run-out (taper)	≤ 1.5 µm
Chuck clamping range	Ø 1.0 - 6.35 mm (incl. 1/8 + 1/4")
Tool change	2 combination wrenches (10 + 13 mm)
Cooling system	Cooling via clamping bracket
Protected against dirt and cooling lubricant	Sealing air 0.5 - 0.8 bar (hose Ø inner/outer 4/6 mm)
Housing material	Stainless steel
Inverter recommendation	e@syDrive® 4438, TV 4538

Subject to change without notice



INDUSTRIAL DRIVES

SycoTec GmbH & Co. KG
 Wangener Strasse 78
 88299 Leutkirch
 Germany

Phone +49 7561 86-0
 Fax +49 7561 86-371
 info@sycotec.eu
 www.sycotec.eu

